



VISION CASIA
SG Y SCG

Suitable for almost any kind of product, Vision Casia SG and SCG machines significantly increase the number of channels and storage capacity, since they can be connected to a master machine or a control module.



ENERGY CLASS
REGULATION (EU)
2019/2018

FEATURES

- Temperature: SG (without cooling unit) SCG (with cooling unit).
- Capacity for 6 and 2 height-adjustable trays with up to 10 channels each.
- FIFO (First In First Out) System. Product dispensing according to loading order.
- Correct sale detection with photocells.
- LED lighting system with on/off programming.
- 1169 x 714 mm glass front door.
- Continuous performance self-testing.
- Flexible setup and programming. Its channel adjustment system allows incorporating new products at any time without using tools.
- Adjustable motor torque for each selection.
- Power mains: 230 V, 50 Hz.
- Estimated energy consumption: 650 watts.

STRUCTURE

- Modular cabinet structure treated against rust and corrosion.
- Vandal-proof security lock with three anchor points.
- Injected foam insulation system to guarantee efficient cooling and lower energy consumption.

PROGRAMMING

- Through a Casia G, CG, GE o CGE.
- Through a control module, TAOS Slim or TAOS 17.



VANDAL-PROOF
LOCK



OPTIMISED
CAPACITY AND
VOLUME



ENERGY-SAVING
LED LIGHTING

VISION SG / SCG CASIA V7

Temperature	Without cooling unit / With cooling unit
Maximum capacity	6 trays of up to 10 channels and 2 trays of up to 7 channels
Elevator	No
Size (mm)	1.830 x 803 x 935
Weight	325 kg
Energy supply	230 V, 50 Hz*
Product in sight	Yes / Privacy adhesive option

*Otras tensiones, consultar.



EASYFLEX
DELIVERY SYSTEM



PRODUCT DELIVERY
DETECTION
PHOTOCELLS



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

