



Coffeemar

BLUETEC
XL 46

CTG
coffee to go

The Coffeemar Bluetec XL 46 model, in addition to a perfect combination of **innovation**, high **performance** and modern **aesthetics**, offers a perfect service for the demand of **coffee to go**.

With its double brewing unit, two separated coffee canisters and a doubled water circuit, it is the only model on the market capable of brewing **14 gr** of coffee, dispensed in **350 ml** of water, in less than **25 seconds**.

All this is made with the **technology** developed by **Jofemar** for its range of Coffeemar machines, which allows the extraction of all the **quality** of the coffee beans, and includes the top features for a vending machine.

CHARACTERISTICS

- Pressure valve in the brewing unit to maintain constant pressure throughout the dispensing cycle.
- Motorised water distributor without solenoid valves.
- Aluminium boiler with encapsulated resistance and sensors, without contact with the water (avoiding O-rings and limescale build-up).
- Extractor for cups up to 80 mm diameter and 117 mm high, 350 ml.
- Dispenser for adjustable stirrers between 75 mm and 115 mm long.
- Self-cleaning of the mixing circuit, product outlet and grinding unit: manual or automatic (programmable).
- Against steam sugar addition system, directly to the cup.
- Constant temperature control in the boiler.
- Smooth closing system on the product collection door.
- Easy cleaning and maintenance of removable elements.
- Delivery of lids for the cup, with the possibility of pre-selection button and price surcharge.
- Double brewing unit, with simultaneous operation, option for two types of coffee, or coffee and tea leaf.

Services	500
Canisters	6 + 2 grano
Selections+preselection	18+2
Whippers	4
Graphic display	92 x 53 mm
Size	1.825 x 755 x 560 mm
Weight	170 kg
Mains water supply	3/4 GAS
Energy supply	230V, 50 Hz*
Maximum power	2.000 watos

*Check for other voltages.



Delivery of lids with optional surcharge in the price.

CONSTRUCTION

- Front in tempered glass embedded in metal, without access to lateral edges.
- Anti-fingerprint stainless steel finish.
- Cabinet in steel treated against corrosion and vandal-proof closing, integrated door in cabin (against crow-bars).

CREDIT MANAGEMENT

- MDB payment systems, JF8 coin acceptor, BT11 banknote reader, J-140 card readers, or other compatible systems.

PROGRAMMING

- General on-site programming using the keyboard, Easy-Flash hand terminal, via PC.
- Storage and retrieval of accounts.

OPTIONS

- Selffeeding water kit (one or two tanks of 25 l each).
- Water filters: water softener or flavour filter.

CAPACITIES

Coffee beans	4.600 g
Powdered milk	1.700 g
Chocolate	1.350 g
Sugar	2.100 g
Freeze dried coffee	700 g
Tea and herbal drinks	1.000 g



VANDAL-PROOF LOCK



OPTIMISED CAPACITY AND VOLUME



ENERGY-SAVING LED LIGHTING



BANKNOTE AND COIN MECHANISM PAYMENT SYSTEMS



MOTORIZED WATER DISTRIBUTOR WITHOUT ELECTROVALVES



PRESSURE VALVE IN THE BREWING UNIT



ALUMINIUM BOILER



TOUCH KEYBOARD



SMUDGE-PROOF STAINLESS STEEL



Ctra. Marcilla km 2
31350 PERALTA. Navarra SPAIN
Tel. +34 948 75 12 12
Fax +34 948 75 04 20
www.jofemar.com

